





℄ SYMMETRY




JIG LOCATE TO MATCH 28F 9001(REF) ON 28W5005(REF)





NOTES:-
BREAK ALL CORNERS 1/16 R EXCEPT WHERE SHOWN AND NOTED OTHERWISE. - ALL FILLETS TO BE 3/16.
MINIMUM WALL THICKNESS TO BE 3/16.



-7 IDENTICAL TO -6 EXCEPT AS SHOWN

CLASS I INSPECTION.

H 49

NOTE: SURFACES INDICATED BY ASTERISK(*) ARE TO RECEIVE A CONVENTIONAL FINISH UNLESS CASTING IS MADE BY PERMANENT MOLD ANTIOCH, ESBRINK OR EQUIVALENT PROCESS.

APPROVED FO[redacted]
TOOLING BY [redacted]

PART No.	STOCK	MATERIAL	SPEC.
-9	FINISHED CASTING	MAKE FROM -7 ROUGH CASTING	
-8	FINISHED CASTING	MAKE FROM -6 ROUGH CASTING	
-7	ROUGH CASTING	AL. ALL.	
-6	ROUGH CASTING	AL. ALL.	

PARTS LIST PER ASSY.

SCALE: 12" = 1'-0"

NAVY: None
FINISH: F-GP

NAME: CHOCK - ARM'T. BRITISH BOMB ADAPTER-CASTING

CONSOLIDATED AIRCRAFT CORP. SAN DIEGO, CALIF.

J 28 A 5200